



busbar work-centre

300-300

Features

- Bending machine is mounted on adjustable lift so that copper can sit on the bench and the machine is adjusted to the centre of the copper.
- Engraved scale on bench top so that distance from end of copper to centre of bend is shown.
- Engraved scale on bench top so that distance from end of copper to cutting position is shown.
- Cutter has centring guide for copper bar.
- Rollers support copper at correct height for punching machine. Electric pump controlled by 2-pedal foot switch.
- Rubber bumper strip round bench.
- Waste collection bins under cutting and punching machine.



Specification	Standard	Optional extras
Cutting capacity	125 x 10	
Punching capacity (thickness)	10	
Punching capacity (maximum diameter)	21	
Bending capacity (maximum width)	150	200
Bending capacity (maximum thickness)	10	15
Bending capacity (max cross-section mm ²)	1200	2250
Bending angle control	visual	electronic or limit-switch
Function selection by rotary valve	3-way	4-way
Supply voltage	220v 1 ph	110v 1 ph
KW rating	0.55	1.5
Maximum pressure (bar / psi)	700 / 10,000	700 / 10,000
Oil flow rate at max pressure (ltr/min)	0.43	1.0
Overall dimensions cm	73 x 115 x 128	
Total weight kg	188	
Wheel diameter (2 wheels with brakes) mm	200	